

### ACRYLIC CAULKING

A one component odourless Acrylic Sealant with minimal shrinkage. Sandable, solvent free and rapid curing allowing over painting if required after a short time.

#### APPLICATION

- Staircases
- Timber floors
- Laminate floors
- Timber doors and windows.
- Around skirting boards
- Can be coated with water or oil based finishes

PLEASE NOTE: Not suitable for surfaces where there is frequent and prolonged water contact.

#### SURFACE PREPARATION

- Surfaces must be dry, sound and clean.
- Free from dust, loose particles, oil and grease.
- Cut seal and nozzle to the required diameter for the job
- Apply with a caulking gun.
- Any excess should be wiped off immediately with water

#### TECHNICAL DATA

Tack Free Time	23°C, 50% H.R.	ca. 10 min
Specific Gravity		ca. 1,70 g/cm <sup>3</sup>
Hardness SHORE A		ca. 40°
Movement Capability		7%
Temperature Resistance		-10°C to +80°C
Application Temperature		5°C to 40°C

**COLOURS** Maple, Oak, Beech, Pine & Wenge

**STORAGE** Store undercover in cool, dry conditions. 5°C - 25°C Protect from frost.

**SHELF LIFE** 18 months from production date in original packaging

**CLEAN UP** Clean tools and surfaces using clean water prior to curing

**PACKAGING** 300 ml cartridge

**DISPOSAL** Keep out of sewer and stormwater lines. In the interest of the environment, please dispose of empty bag and materials as trade waste in accordance with local authority guidelines.

**SAFETY INFORMATION** The end-user of this product must first read the latest version of the Safety Data Sheets at [www.acouslime.com.au](http://www.acouslime.com.au) before this product can be used.

DISCLAIMER - The end use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven to be faulty. The manufacturer is NOT responsible for any loss or damage arising from incorrect usage of this product. The information contained herein is provided in good faith and to best of Acouslime Pty Ltd knowledge is true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for an application