

Product name : SOLID2K**XD 5200****Description**

Solid 2k is the hardener for Solid range water-based coatings for wooden floors.

Version

XD 5200 Solid 2k

Application possibilities

It can be used in compound with Solid range water-based coatings for interior and exterior.

Peculiarities

It is isocyanate aliphatic resin-based and it does not yellow out. It produces a chemical reaction with coating resins improving considerably their foot traffic resistance properties along with the surface chemical and physical resistance.

Application instructions

Read the technical sheets of the specific products.

Product preparation

Ready to use

Chemical and physical characteristics at 23° C

Appearance	Clear transparent liquid
Colour	From transparent to straw-coloured

Application instructions

Add a quantity of product according to product specifications: add Solid 2k while stirring and mixing vigorously for one minute.

Catalysis

The addition of the Solid 2k hardener inside the product generates a chemical reaction. After the addition, apply it within 4 hours maximum (3 hours during summer). Read the technical sheets of the specific products before application.

Tools cleaning

Clean every tool immediately after use. Solid 2k can be easily removed (if not already dried) with any acetone-based solvent.

Storage

The product reacts with moisture. It should be exposed to the air only for the minimum time necessary. Keep container tightly closed after use.

Waste disposal

The exceeding and useless material must be disposed of as special waste. Do not empty into drains.

Personal protective equipment

Wear protective rubber, latex or polyethylene gloves. It can release in the air small amounts of solvent. Please, ventilate the room during the application.

Package

0,5 L bottles.

Storage

The product keeps inalterated its characteristics throughout 18 months if stored inside its original package, tightly closed, at 23° C. Do not store in damp or wet places at temperatures exceeding 35° C.

Packaging recycling

The plastic package must be recycled in the right dumper or recycling point (according to the municipal garbage collection). Please, check that the package is empty and dry, with the minimum possible product quantity inside.

Warnings

Data and information inside this Technical Sheet represent our current best knowledge and experiences and cannot be used as a warranty due to the diversity of materials existing on the market and the difficult monitoring of application conditions.

The final user must check if the product corresponds to his own needs in relation to application tools, supports and environmental conditions of application and drying. In any case, Renner Italia S.p.A. guarantees the constant quality of its products. Renner Italia S.p.A. reserves the right to modify and update this technical sheet according to its own needs. Customers shall verify to own the updated version of this sheet.

CAREFULLY READ AND UNDERSTAND THIS TECHNICAL SHEET BEFORE USING THE PRODUCT