



## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **XD3094**  
Product name: **SOLIDOILNATURE - WB OIL FOR PALE PARQUET**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **FURNITURE OIL**

#### 1.3. Details of the supplier of the safety data sheet

Name: **RENNER ITALIA S.P.A.**  
Full address: **Via Ronchi Inferiore, 34**  
District and Country: **40061 Minerbio (BO) Italia**  
Tel.: **+39 051-6618211**  
Fax: **+39 051-6606312**

e-mail address of the competent person responsible for the Safety Data Sheet

**sds@renneritalia.com**

#### 1.4. Emergency telephone number

For urgent inquiries refer to

**RENNER ITALIA S.p.A. - Tel. +39 051-6618211 (dal lunedì al venerdì dalle 8.30 - 13.00 e dalle 14.00 - 17.30)**

**ITALIA**

**Centro antiveneni Milano - Tel. +39 02-66101029**

**Centro antiveneni Firenze - Tel. +39 055-7947819**

**CROATIA**

**Služba za izvanredna stanja (112)**

**Centar za kontrolu otrovanja (01/2348-342)**

**HUNGARY**

**Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ)**

**1096 Budapest, Nagyvárad tér 2.**

**Telefon: +36 1 476 6464 (8-16 óráig), +36 80 201 199 (éjjel-nappal hívható) magyar nyelven**

**LATVIA**

**Valsts ugunsdzēsības un glabšanas dienests: (+371) 112**

**Saindešanas un zalu informācijas centrs: (+371) 67042473 (visu diennakti)**

**LITHUANIA**

**Apsinuodijimų kontrolės ir Informacijos biuras visą parą tel. (8 5) 236 2052**

**Bendras pagalbos telefonas: 112**

**NORWAY**

**Emergency number: 113**

**POLSKA**

**Numer telefonu alarmowego: +48 22 615 27 51**

**PORTUGAL**

**Centro de Informação Anti-Venenos: +351 808 250 143**

**BULGARIA - България**

**Национален център по токсикология, МБАЛСМ "Пирогов"**

**телефон: +359 2 9154 233**

**AUSTRALIA & NEW ZEALAND**

**Poisons information Centre, Australia wide: Phone 13 11 26 - H24 Service**

**Police or Fire Brigade: Phone 000 Or New Zealand: 0800 764 766**

**SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.

Hazard classification and indication: --

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.  
**EUH208** Contains: 2-METHYL-4-ISOTHIAZOLIN-3-ONE  
May produce an allergic reaction.

Precautionary statements:

**P102** Keep out of reach of children.  
**P101** If medical advice is needed, have product container or label at hand.

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :	49,82
Limit value:	140,00
- Catalysed with :	5,00 % HARDENER FOR WATERBORNE COATINGS

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>DIPROPYLENE GLYCOL MONOMETHYL ETHER</b>		
CAS	34590-94-8 $2 \leq x < 3$	<b>Substance with a community workplace exposure limit.</b>
EC	252-104-2	
INDEX		
Reg. no.	01-2119450011-60-xxxx	
<b>2-METHYL-4-ISOTHIAZOLIN-3-ONE</b>		
CAS	2682-20-4 $0 \leq x < 0,0015$	<b>Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1</b>
EC	220-239-6	
INDEX	613-167-00-5	
Reg. no.		

The full wording of hazard (H) phrases is given in section 16 of the sheet.



## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

**INHALATION:** Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM-SZCSM együ., Ttes rendelet módosításáról.
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	LIETUVOS HIGIENOS NORMA HN 23:2011 „CHEMINIŲ MEDŽIAGŲ PROFESINIO POVEIKIO RIBINIAI DYDŽIAI. MATAVIMO IR POVEIKIO VERTINIMO BENDRIEJI REIKALAVIMAI. Nr. V-695/A1-272, 2018-06-12, paskelbta TAR 2018-06-15, i. k. 2018-09988
LVA	Latvija	Ķīmisko vielu aroda ekspozīcijas robežvērtības (AER) darba vides gaisā 2018
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de implementatie van Richtlijn 2017/164 in Bijlage XIII
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SVK	Slovensko	Nariadenie vlády č. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred rizikami súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Uradni list Republike Slovenije 20.12.2019 - Uradnem listu RS št. 78/19 -PRAVILNIK o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
TUR	Türkiye	12.08.2013 Tarihi, 28733 Sayılı, Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

### SECTION 8. Exposure controls/personal protection ... / >>

TLV-ACGIH 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.  
ACGIH 2020

#### DIPROPYLENE GLYCOL MONOMETHYL ETHER

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV	BGR	308	50			SKIN
TLV	CZE	270	43,74	550	89,1	SKIN
AGW	DEU	310	50	310	50	
MAK	DEU	310	50	310	50	
VLA	ESP	308	50			SKIN
TLV	EST	308	50			SKIN
VLEP	FRA	308	50			SKIN
TLV	GRC	600	100	900	150	
AK	HUN	308				
GVI/KGVI	HRV	308	50			SKIN
VLEP	ITA	308	50			SKIN
RD	LTU	300	50	450	75	SKIN
RV	LVA	308	50			SKIN
TLV	NOR	300	50			SKIN
TGG	NLD	300				
VLE	PRT	308	50			SKIN
NDS/NDSch	POL	240		480		SKIN
TLV	ROU	308	50			SKIN
NPEL	SVK	308	50			SKIN
MV	SVN	308	50			SKIN
ESD	TUR	308	50			SKIN
WEL	GBR	308	50			SKIN
OEL	EU	308	50			SKIN
TLV-ACGIH		606	100	909	150	SKIN

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	19	mg/l
Normal value in marine water	1,9	mg/l
Normal value for fresh water sediment	70,2	mg/kg
Normal value for marine water sediment	7,02	mg/kg
Normal value for water, intermittent release	190	mg/l
Normal value of STP microorganisms	4168	mg/l
Normal value for the terrestrial compartment	2,74	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				36				
				mg/kg bw/d				
Inhalation				37,2				308
				mg/m <sup>3</sup>				mg/m <sup>3</sup>
Skin				121				283
				mg/kg bw/d				mg/kg bw/d

### SECTION 8. Exposure controls/personal protection ... / >>

#### 1,2-PROPANEDIOL

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
GVI/KGVI	HRV	474	150			
RD	LTU	7				
RV	LVA	7				
TLV	NOR	79	25			
NDS/NDSch	POL	100				INHAL
WEL	GBR	10				Particulates

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	260	mg/l
Normal value in marine water	26	mg/l
Normal value for fresh water sediment	572	mg/kg
Normal value for marine water sediment	57,2	mg/kg
Normal value for water, intermittent release	183	mg/l
Normal value of STP microorganisms	20000	mg/l
Normal value for the terrestrial compartment	50	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute	Acute	Chronic	Chronic	Acute	Chronic	Chronic	
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation			10	50			10	168
			mg/m <sup>3</sup>	mg/m <sup>3</sup>			mg/m <sup>3</sup>	mg/m <sup>3</sup>
Skin							10	

#### 2-METHYL-4-ISOTHIAZOLIN-3-ONE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
MAK	DEU	0,2				INHAL
MV	SVN	0,05				

#### DIETHYLENE GLYCOL MONOETHYL ETHER

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	1,98	mg/l
Normal value in marine water	0,198	mg/l
Normal value for fresh water sediment	7,32	mg/kg
Normal value for marine water sediment	0,732	mg/kg
Normal value of STP microorganisms	500	mg/l
Normal value for the food chain (secondary poisoning)	444	mg/kg
Normal value for the terrestrial compartment	0,34	mg/kg/d

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute	Acute	Chronic	Chronic	Acute	Chronic	Chronic	
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				50				
				mg/kg bw/d				
Inhalation			18	37			30	61
			mg/m <sup>3</sup>	mg/m <sup>3</sup>			mg/m <sup>3</sup>	mg/m <sup>3</sup>
Skin				25				83
				mg/kg bw/d				mg/kg bw/d

##### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.  
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

**SECTION 8. Exposure controls/personal protection ... / >>**

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties**

NOTE: Determination of the flash point may be NA (not applicable), the product being non flammable.

**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	liquid	
Colour	white	
Odour	characteristic	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point	> 65 °C	
Boiling range	Not available	
Flash point	> 60 °C	
Evaporation Rate	Not available	
Flammability of solids and gases	not applicable	
Lower inflammability limit	Not available	
Upper inflammability limit	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	1,02	
Solubility	partially soluble in water	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not available	
Decomposition temperature	Not available	
Viscosity	Not available	
Explosive properties	not applicable	
Oxidising properties	not applicable	

**9.2. Other information**

Total solids (250°C / 482°F)	22,44 %	
VOC (Directive 2004/42/EC) :	5,12 % - 52,18	g/litre
VOC (volatile carbon) :	2,86 % - 29,16	g/litre



## SECTION 10. Stability and reactivity

### PHENETHYL ALCOHOL

PHENETHYL ALCOHOL: Incompatible materials: strong oxidising agents, strong acids.

### 1-HYDROXYPYRIDINE-2-THIONE ZINC

1-HYDROXYPYRIDINE-2-THIONE ZINC - Keep away from light. Incompatible materials: oxidising agents, heavy metals and reducing agents.

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### DIPROPYLENE GLYCOL MONOMETHYL ETHER

Forms peroxides with: air.

### 1,2-PROPANEDIOL

Hygroscopic. Stable in normal conditions of use and storage.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

### DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.

### 1,2-PROPANEDIOL

May react dangerously with: acid chlorides, acid anhydrides, oxidising agents.

### DIETHYLENE GLYCOL MONOETHYL ETHER

DIETHYLENE GLYCOL MONOETHYL ETHER - it can form explosive mix with air in presence of high temperature ( $T > 94^{\circ}\text{C}$ )

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

### DIPROPYLENE GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat. Possibility of explosion.

#### 10.5. Incompatible materials

### GERIANOL

Avoid materials: oxidant agents, acylic halogenates, anhydrides.

#### 10.6. Hazardous decomposition products

### 1,2-PROPANEDIOL

May develop: carbon oxides.

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

Information not available

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available





### SECTION 11. Toxicological information ... / >>

#### Interactive effects

Information not available

#### ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)  
ATE (Oral) of the mixture: Not classified (no significant component)  
ATE (Dermal) of the mixture: Not classified (no significant component)

DIPROPYLENE GLYCOL MONOMETHYL ETHER  
LD50 (Oral) > 5000 mg/kg  
LD50 (Dermal) 9510 mg/kg

1,2-PROPANEDIOL  
LD50 (Oral) 22000 mg/kg  
LD50 (Dermal) > 2000 mg/kg

POLYETHYLENE WAX  
LD50 (Oral) > 2000 mg/kg

2-METHYL-4-ISOTHIAZOLIN-3-ONE  
LD50 (Oral) 183 mg/kg  
LD50 (Dermal) 218 mg/kg  
LC50 (Inhalation) 0,53 mg/l/4h

DIETHYLENE GLYCOL MONOETHYL ETHER  
LD50 (Oral) 6031 mg/kg  
LD50 (Dermal) 9143 mg/kg  
LC50 (Inhalation) 0,02 mg/l 8 h

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

#### SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

#### RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.  
Contains:  
2-METHYL-4-ISOTHIAZOLIN-3-ONE

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity

#### DIPROPYLENE GLYCOL MONOMETHYL ETHER

LC50 - for Fish	> 1000 mg/l/96h <i>Poecillia reticulata</i>
EC50 - for Crustacea	1919 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	> 969 mg/l/72h <i>Pseudokirchneriella subcapitata</i>
Chronic NOEC for Crustacea	> 0,5 mg/l <i>Daphnia magna</i>
Chronic NOEC for Algae / Aquatic Plants	969 mg/l <i>Pseudokirchneriella subcapitata</i>

#### 1,2-PROPANEDIOL

LC50 - for Fish	40613 mg/l/96h <i>Onchorynchus mykiss</i>
EC50 - for Crustacea	18340 mg/l/48h <i>Ceriodaphnia dubia</i>
Chronic NOEC for Crustacea	13020 mg/l

#### POLYETHYLENE WAX

LC50 - for Fish	> 100 mg/l/96h
-----------------	----------------

#### 2-METHYL-4-ISOTHIAZOLIN-3-ONE

LC50 - for Fish	> 150 mg/l/96h <i>Danio rerio</i>
EC50 - for Crustacea	0,87 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0,157 mg/l/72h <i>Selenastrum capricornutum</i>
Chronic NOEC for Crustacea	0,044 mg/l
Chronic NOEC for Algae / Aquatic Plants	0,0104 mg/l <i>Pseudokirchneriella subcapitata</i>

#### DIETHYLENE GLYCOL MONOETHYL ETHER

LC50 - for Fish	10000 mg/l/96h <i>Lepomis macrochirus</i>
EC50 - for Crustacea	> 1982 mg/l/48h <i>Daphnia magna</i>

### 12.2. Persistence and degradability

#### DIPROPYLENE GLYCOL MONOMETHYL ETHER

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

#### 1,2-PROPANEDIOL

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

#### 2-METHYL-4-ISOTHIAZOLIN-3-ONE

NOT rapidly degradable

#### DIETHYLENE GLYCOL MONOETHYL ETHER

Rapidly degradable	> 80%
--------------------	-------

### 12.3. Bioaccumulative potential

#### DIPROPYLENE GLYCOL MONOMETHYL ETHER

Partition coefficient: n-octanol/water	0,0043
--	--------

#### 1,2-PROPANEDIOL

Partition coefficient: n-octanol/water	-1,07
BCF	0,09

#### 2-METHYL-4-ISOTHIAZOLIN-3-ONE

Partition coefficient: n-octanol/water	-0,32
--	-------

#### DIETHYLENE GLYCOL MONOETHYL ETHER

Partition coefficient: n-octanol/water	-0,8
BCF	< 100

**SECTION 12. Ecological information ... / >>****12.4. Mobility in soil**

DIPROPYLENE GLYCOL MONOMETHYL ETHER  
Partition coefficient: soil/water 0,28

1,2-PROPANEDIOL  
Partition coefficient: soil/water 0,46

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.  
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  
CONTAMINATED PACKAGING  
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number**

Not applicable

**14.2. UN proper shipping name**

Not applicable

**14.3. Transport hazard class(es)**

Not applicable

**14.4. Packing group**

Not applicable

**14.5. Environmental hazards**

Not applicable

**14.6. Special precautions for user**

Not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information**

Only for uses exempt from EU DIRECTIVE 2004/42/CE.

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product  
Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 2</b>	Acute toxicity, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>Skin Corr. 1C</b>	Skin corrosion, category 1C
<b>Skin Sens. 1A</b>	Skin sensitization, category 1A
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>H330</b>	Fatal if inhaled.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H317</b>	May cause an allergic skin reaction.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>EUH210</b>	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008



### SECTION 16. Other information ... / >>

- DNEL: Derived No Effect Level- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Regulation (EU) 2020/217 (XIV Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in



### SECTION 16. Other information ... / >>

Section 11.Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 05 / 07 / 08 / 09 / 10 / 11 / 12 / 15 / 16.