

Product name: **SOLIDWAXMAT****XD 4070**

Description

SolidWaxMat is a maintenance wax for wooden surfaces, coated with products for matt wood floorings.

Version

XD 4070 SolidWaxMat with matt effect.

Fields of application

SolidWaxMat is suitable for regular maintenance of wood floorings, treated with matt, oil or zero gloss water-based coatings of Solid range (SolidZero, SolidNature and SolidOil) and with oil treatment or with a treatment lower than 20 gloss of the professional range.

Main features

Made of oily resins and waxes in water emulsion, it has low solvents content and it does not contain substances, which can be harmful to the user's health and the environment. It restores the colour of the floor, avoiding its deterioration.

Application method

Short pile roller, cloth, mop.

Product preparation

Ready to use; read the instructions carefully.

Certifications or properties of dry film in system: 3 coats of SolidOil

Complying with requirements for high traffic according to the following standards:

- Resistance to abrasion UNI EN 15185 | Resistance to chemical agents UNI EN 13442 | Resistance to dirt UNI 9300

Chemical-physical features at 23°C

Aspetto	Whitish liquid	pH	8 +/- 1
---------	----------------	----	---------

Instructions

- *For a regular daily treatment.* Clean the floor with SolidClean according to its technical data sheet. Before the application of the wax, the floor must be completely dry. Dilute SolidWaxMat in 1:1 ratio with water and apply with a soft cloth soaked with product and then rung out. Let it dry off. Rinsing and polishing are not necessary. It is possible to trample on the floor after its drying.
- *For the extraordinary treatment of surfaces matted by wear.* Proceed as described above. Use SolidWaxMat without dilution and apply it by mop or soft cloth soaked with product, making sure of spreading it evenly. Let it dry off. Rinsing and polishing are not necessary. Wait at least for one hour before trampling.

Packaging

1 L plastic bottle.

Storage

The product keeps its features unaffected throughout 18 months if stored inside its original packaging, tightly closed at 23°C. Do not store in damp or wet places at a temperature above 35°C.

Packaging recycling

The plastic packaging must be recycled in the right dumpster or recycling point (according to the municipal garbage collection). Please, check that the packaging is empty and dry, with the minimum possible product quantity inside.

Warnings

Data and information inside this technical sheet represent our current best knowledge and cannot be used as a warranty due to the diversity of materials existing on the market and the difficult monitoring of application conditions. The final user must check if the product corresponds to his own needs in relation to application tools, supports and environmental conditions of application and drying. In any case, Renner Italia S.p.A. guarantees the constant quality of its products. Renner Italia S.p.A. reserves the right to modify and update this technical sheet according to its own needs. Customers shall verify to have the updated version of this sheet.
ALWAYS CONSULT THE SAFETY DATA SHEET OF THE PRODUCT BEFORE USING IT.