

**LVT FIBRE REINFORCED ACRYLIC ADHESIVE**

Solvent free Adhesive for bonding LVT Tiles onto absorbent subfloors  
 Quick with a strong initial tack and excellent adhesion with strong dimensional stability.  
 Suitable for underfloor heating. For indoor use only.



**TECHNICAL DATA**

Technical Data ( 20°C – 60% R.H.)			
Appearance	Beige paste	Trowel Size	2mm V Notch
Density	1.29 kg per litre	Application temperature	From +10C to max 35°C
Waiting time	0 -10 minutes	Coverage per Tub	40 - 48 m2
Open time	20 -30 minutes	Tools cleaning	Immediately after use with water
Light traffic	5 – 6 hours	Package available	12 kg tub
Complete curing	3 days	storage	12 months in original sealed container at temperature >10°C Frost Sensitive

**SUBFLOOR PREPARATION**

Can be applied onto any absorbent subfloor in a good condition. Must be solid, even, smooth, free from dust, oils and surface contaminants. All defective host substrate must be removed before application. The maximum acceptable humidity level is < 2.5% (2.2% in case of underfloor heating) Uneven surfaces must be levelled with a suitable Acouslime product compatible with Acrylic adhesives. Under Floor heating must be prepared according to the supplier instructions. Switch off heating 24 hours before laying. Follow manufacturers guidelines for installation on underfloor heating. Uneven surfaces must be levelled with a suitable Acouslime product compatible with Acrylic adhesives. Any dusty or highly absorbent surfaces will need to be consolidated. Please ring office for suitable compatible product.

**APPLICATION**

Acclimatize both the adhesive and flooring at least 24 hours before laying. It is important to remove the resilient flooring from the packaging to allow any tensions to dissipate by laying the flooring freely apply. It is important to stir Acouslime LVT Fibre Reinforced thoroughly before use. Apply with the appropriate trowel, lay the LVT tiles or strips within 20 – 30 minutes Periodically check the back of the LVT for adhesion. If the open time has been exceeded and transfer of adhesion not enough, remove the adhesive and repeat the application. (Continued next page)

**APPLICATION** - Continued

Once laid use a 60kg roller over the floor from the centre towards the outer edges of the room to expel any air bubbles that may be present. Fresh adhesive can be cleaned with water, once dry use an adhesive remover. Wear suitable gloves.

Please dispose of any unused product responsibly and empty containers in accordance with local regulations. Keep out of the environment including waterways.

**NOTES**

- PRODUCT FOR PROFESSIONAL USE
- Follow flooring manufacturers installation instructions for laying.
- Do not use for floors subject to constant water.
- For Indoor use only
- The waiting time can be longer if the temperature is low and humidity high
- Store at temperatures above +5°C
- Strictly adhere to the instructions in this document.

**[To be read in conjunction with Safety Data Sheet on our website.](#)**

The information contained herein is to the best of our knowledge and belief, accurate and reliable as of the date the data was compiled. However no representation, warranty, or guarantee is made regarding its accuracy, reliability, or completeness by Acouslime Pty Ltd or any of its affiliates. It is the responsibility of the user to assure the suitability and completeness of such information and any depicted product for the particular use of the user. Acouslime Pty Ltd and its affiliates accept no liability for any loss or damage that may occur from the use of the information or any depicted product. Acouslime Pty Ltd and its affiliates specifically and expressly disclaim any and all warranties, express or implied, including merchantability, fitness for a particular purpose and freedom from claims of infringement of the rights of others associated with the sale or use of any product depicted. Acouslime Pty Ltd and its affiliates further disclaim any liability for consequential or incidental damages of any kind, including lost