

**PRESSURE SENSITIVE WATERBASED ACRYLIC ADHESIVE
WITH PERMANENT TACK**

For use with Carpet Tiles and Carpet.



FLOORING TYPES

Suitable for any type of substrate including underfloor heating. This product allows for the easy removal of the floor covering even after a long period of time. Thanks to the Adhesive's permanent tack the original floorcovering can be repositioned or replaced. even after a long period of time.

TECHNICAL DATA

Technical Data (20°C – 60% R.H.)			
Appearance	Dense paste	Trowel Size	2mm V Notch
Density	1.10 kg per litre	Application temperature	From +10C to max 35°C
pH	8	Coverage per Tub - Trowel (5% dilution for roller)	50 - 80m2 per tub
Dilution to enable applying with roller	5% max.	Storage	12 months in original sealed container at temperature >10°C Frost Sensitive
Waiting time	When Adhesive becomes transparent, it is ready for use in 1-2 hours approx. Up to 12 hours according to environmental conditions	Tools cleaning	Immediately after use with water
Walking time	Immediately after laying	Package available	12 kg tub
Ready for traffic	Immediately after laying		

SUBFLOOR PREPARATION

Can be applied onto any type of subfloor in a good condition. Must be solid, smooth, free from dust, oils and surface contaminants. All defective host on subfloor must be removed before application. Concrete substrates must be even, resistant to pressure and without dust and moisture. The moisture on concrete slabs must not exceed 2.5 – 3.0% Uneven surfaces must be levelled with a suitable Acouslime product compatible with Acrylic adhesives. Any dusty or highly absorbent surfaces will need to be consolidated. Please ring office for suitable product.

Before starting the installation make sure the adhesive, flooring to be laid and substrate are acclimatised to the same temperature. It is important to remove the resilient flooring from the packaging a few hours before laying to allow any tensions due to packaging to dissipate by laying the flooring freely or at least loosening the rolls.

APPLICATION

Apply Acouslime Pressure Sensitive Tack uniformly over the whole area using a 2mm V notch trowel. If a roller is used the adhesive would need to be diluted by 10% Wait until the adhesive becomes transparent; 1 – 12 hours depending on environmental conditions to enable optimal tacking properties - then proceed to lay the resilient floor taking care to press (massage) the surface. When laid use a roller over the floor from the centre towards the outer edges of the room to expel any air bubbles that may be present. Fresh adhesive can be cleaned with water, once dry use an adhesive remover.

Wear suitable gloves.

Please dispose of any unused product responsibly and empty containers in accordance with local regulations. Keep out of the environment including waterways.

NOTES

- PRODUCT FOR PROFESSIONAL USE
- Follow flooring manufacturers installation instructions for laying.
- For Indoor use only
- The waiting time can be longer if the temperature is low and humidity high
- Store at temperatures above +5°C Frost sensitive
- Strictly adhere to the instructions in this document.

[To be read in conjunction with the Safety Data Sheet shown on our website.](#)

The information contained herein is to the best of our knowledge and belief, accurate and reliable as of the date the data was compiled. However no representation, warranty, or guarantee is made regarding its accuracy, reliability, or completeness by Acouslime Pty Ltd or any of its affiliates. It is the responsibility of the user to assure the suitability and completeness of such information and any depicted product for the particular use of the user. Acouslime Pty Ltd and its affiliates accept no liability for any loss or damage that may occur from the use of the information or any depicted product. Acouslime Pty Ltd and its affiliates specifically and expressly disclaim any and all warranties, express or implied, including merchantability, fitness for a particular purpose and freedom from claims of infringement of the rights of others associated with the sale or use of any product depicted. Acouslime Pty Ltd and its affiliates further disclaim any liability for consequential or incidental damages of any kind, including lost profits.