

# **CONSTRUCTION ADHESIVE**

Technical Data Sheet

## QUICK SETTING VERY FAST AND STRONG INITIAL TACK





#### **FEATURES**

- Solvent Free
- Waterbased
- Strong mounting adhesive

#### **AREAS OF APPLICATION - SUITABILITY**

- On absorbent surfaces such as concrete, timber, stone.
- PVC ( Not suitable for PE, PP, and PTFE)
- Vertical Bonding
- For Skirting boards and other profiles
- Plaster board or similar.
- Metal profiles

#### NOTE

- ONE SURFACE MUST BE ABSORBENT
- Not for Surfaces continually exposed to water or humidity

## **TECHNICAL DATA**

Technical Data (20°C – 60% R.H.)			
Appearance	White paste	Indicative yield	Approx 10Lm for 6mm bead
Density	1.35kg per litre	Application temperature	From +5°C to +35°C
Open time	5 -10 minutes	Tool cleaning	Immediately after use with water
Setting time	Immediate	Storage	12 months in original sealed container at temperature >10°C Frost Sensitive
Initial tack	~ 120kg/m2	Package size	310ml cartridges

## **APPLICATION**

Make sure the surface to be bonded is in optimal condition, flat, clean, free of dust and loose parts and not subject to rising damp.

Apply Acouslime Construction Adhesive with the appropriate canister gun for small quantities or for continuous beading, on only one of the two surfaces to be bonded. Immediately join the parts and place them applying an even pressure. Use a support for fixing heavy materials until the adhesive is completely dry. Repositioning of the glued materials is possible if done within 10 minutes.

Page **1** of **2** 

Ph: +61 7 3484 0606 QLD 23 Commerce Circuit, Yatala 4207



## **CONSTRUCTION ADHESIVE**

Technical Data Sheet

## **CLEANING**

Any surplus residue of the product, while fresh, can be cleaned with water. Use a spatula to remove any fresh adhesive residue along the edges of the glued object.

Once hardened, Acouslime Construction Adhesive can be overcoated with either waterbased or solvent based coatings.

## **SAFETY RULES**

PRODUCT FOR PROFESSIONAL USE. Strictly adhere to what is stated on the labelling and consult Safety Data Sheets before using the product.

## DISPOSAL

Dispose of unused product and empty packaging in accordance with Australian standards. Keep out of waterways.

To be read in conjunction with the Safety Data Sheet shown on our website

The information contained herein is the to the best of our knowledge and belief, accurate and reliable as of the date the data was complied. However no representation, warranty, or guarantee is made regarding its accuracy, reliability, or completeness by Acouslime Pty Ltd or any of its affiliates. It is the responsibility of the user to assure the suitability and completeness of such information and any depicted product for the particular use of the user. Acouslime Pty Ltd and its affiliates accept no liability for any loss or damage that may occur from the use of the information or any depicted product. Acouslime Pty Ltd and its affiliates specifically and expressly disclaim any and all warranties, express or implied, including merchantability, fitness for a particular purpose and freedom from claims of infringement of the rights of others associated with the sale or use of any product depicted. Acouslime Pty Ltd and its affiliates further disclaim any liability for consequential or incidental damages of any kind, including lost profits

Rev 03 – 11/05/2020 Page **2** of **2** 

Ph: +61 7 3484 0606 QLD 23 Commerce Circuit, Yatala 4207